

Farrell Engineering Ltd

Westbury House, 23-25 Bridge Street, Pinner HA5 3HR United Kingdom

Tel : 0044-208-3432 3291 Fax : 044-208-9657586

Email : chan@farrellengineering.com







Category	:-	Pressure Die Casting Machines (PDC)	Serial No	:-	10068260
Model	:-	H 400 D2	Country	:-	
Make	:-	Buhler	Type of Machine	:-	Horizontal Cold Chamber Die Casting Machine
Year	:-		Weight	:-	0.0
Dimensions	:-		Power	:-	
Location	:-	Mumbai Warehouse,India	Asking Price	:-	On Request

Specification :-

Buhler Horizontal Cold Chamber Die Casting Machine Model H-400-D2 with Direct Injection System

Specifications:

Locking force (nominal) Mp 400

Locking Force (strain gauge) Mp 400+ max.10%

Injection force (with intensifier) adj. Mp 38,5

Hyd. Ejection force Mp 22

Die Mounting Plates H X V mm 920 x 980 in 36 1/4 x 38 1/2

Space Between tie bars H X V mm 580 x 640 in. 22 7/8 x 25 1/4

Tie bar Diameter mm 120 in 4 3/4

Max. Die height mm 750 in 29 1/2

Max. Die height (With mot. Die height) mm 725 in 28 1/2

Min. die height mm 200 in 7 7/8

Die opening stroke mm 600 in 23 5/8

Injection Plunger stroke mm 400 in 15 3/4

Ejector Stroke, adj. mm 145 in 5 3/4

Free cycle time sec. 7

Motor Capacity (22 kw) Hp 30 (22KW)

Machine area m 6.1 x 1.65 ft. 20 1/4 x 5 1/2

Machine Weight * tons 12,5

Hydraulic fluid contents litres (+,-) 650 Imp. Gallons (+,-) 121

Production data

Plunger Diameter	60mm 2.36 in.	70mm 2.76 in.	80mm 3.15in.	90mm 3.54 in.	100mm 3.94 in	110mm 4.33 in
Short capacity for Aluminum	2 kp 4.4 lbs.	2.7 kp 5.9 lbs.	3.6 kp 7.9 lbs.	4.5 kp 9.9 lbs	5.6 kp 12.3 lbs	6.8 kp 15 lbs

Max. injection pressure	1360 Kp/cm² 19300 lbs/sq.in	1000 Kp/cm2 14200 lbs/sq.in	765 Kp/cm2 10870 lbs/sq.in	605 Kp/cm2 8700 lbs/sq.in	490 Kp/cm2 6950 lbs/sq.in	405 Kp/cm2 5750 lbs/sq.in
Nom. Casting area at above injection pressure	290 cm2 45 sq.in.	400 cm2 62 sq.in.	520 cm2 80.5 sq.in.	660 cm2 102 sq.in.	815 cm2 126 sq.in.	985 cm2 155 sq.in.

* Metric tons at 2205 lbs.

* Shot capacity is calculated: plunger area x plunger stroke x 75% filling rating specific gravity for liquid Aluminum = 2,5 or 0,09lbs/sg.in.

For magnesium alloys multiply by 0.65 for zinc alloys multiple by 2.5

For copper base alloys multiply by 3.2

* Nom. Casting area at injection pressure of 250 kp/cm2 (3500 lbs/sq.in.) = 1600 cm2 (154 sq.in)

Specifications are subject to modifications with notice.

Description :-