





























LIEBHERR		Kuchgewichtstabelle		WC 201	
		tabulka vyrovnaných závaží		FA 4284/95	
HL	Pos.WR	Pos.WL	HL	Pos.WR	Pos.WL
000000 000000	110	341	000000 000000	000000 000000	000000 000000
000000 000000	000000 000000	000000 000000	000000 000000	000000 000000	000000 000000
000000 000000	000000 000000	000000 000000	000000 000000	000000 000000	000000 000000
000000 000000	000000 000000	000000 000000	000000 000000	000000 000000	000000 000000

HL = Maßhöhe  
 Pos.WR = Kuchgewicht rechte  
 pos.lie = vyrovnané závaží vpravo  
 Pos.WL = Kuchgewicht linke  
 pos.lie = vyrovnané závaží vľavo



Video :-

please click here for video no. 01	
please click here for video no. 02	
please click here for video no. 03	
please click here for video no. 04	
please click here for video no. 05	
please click here for video no. 06	
please click here for video no. 07	
please click here for video no. 08	

Category	:-	Gear Related Machines	Serial No	:-	
Model	:-	WSC 251	Country	:-	Germany
Make	:-	Liebherr	Type of Machine	:-	Six Axis CNC Gear Shaping Machine With Adjustable Taper 10 degree
Year	:-	1995	Weight	:-	0.0
Dimensions	:-		Power	:-	
Location	:-	Mumbai WareHouse, India	Asking Price	:-	On Request

Specification :-

**Six AXIS CNC Gear Shaper With 10 Degree Adjustable Facility (CNC B Axis).**  
**Very Unique Machine with Extra Raiser block 200 mm.**  
**SPUR Hydrostatic spindle guide.**  
**Workpiece clamping hydraulic.**

This machine is being offered in as is condition Old Original Liebherr CNC System is Discarded. We can also offer it with an optional rebuild, recontrol or recertification. We Shall Carry Out The Following Process If You place order For Retroffting.All recontrolled and recertified machines are fully cleaned. All moving slides, spindles and parts handling systems are inspected for problems. Any gibs or adjustable backlash systems are adjusted to the best possible settings. All hydraulic, coolant, lubrication and pneumatic systems are checked for proper functionality and leaks. All filters are replaced. All worn hoses, broken cables, connectors, buttons, lamps and wires are replaced. All guarding is installed and checked. All machine cycles are tested. Parts are cut to verify the machine capability. Charts from the test cutting are documented for your viewing

### **Technical Data:**

**Max. Wheel Diameter: 250 mm**

**Gear Width: 80 mm**

**Max. Module: 6**

**Min. Module: 0.5**

Max. distance between table and spindle-nose: 310 mm

Description :--