

Farrell Engineering Ltd

Westbury House, 23-25 Bridge Street, Pinner HA5 3HR United Kingdom

Tel : 0044-208-3432 3291 Fax : 044-208-9657586

Email : chan@farrellengineering.com





Category	:-	Gear Hobbers	Serial No	:-	
Model	:-	402	Country	:-	Germany
Make	:-	Liebherr	Type of Machine	:-	Heavy Production Gear Hobber
Year	:-		Weight	:-	0.0
Dimensions	:-		Power	:-	
Location	:-	Mumbai Warehouse,India	Asking Price	:-	On Request

Specification :-

MAXIMUM DIAMETER GEAR CUT: 16"
MAXIMUM RATED D.P. (MODULE) IN STEEL: 3.18 DP
MAXIMUM AXIAL TRAVEL: 12"
MINIMUM NUMBER OF TEETH: 6
DIAMETER OF WORK TABLE: 16"
DIAMETER OF INDEX WORM WHEEL: 15.75"
DIAMETER OF CENTER BORE IN WORK TABLE: 4"
DISTANCE BETWEEN CENTERLINE OF HOB AND WORK ARBOR:
12 MAXIMUM / 1.25" MINIMUM
TAPER IN TABLE CENTER BORE &HOB ARBOR: 5 MT
MAXIMUM DIAMETER / LENGTH OF HOB: 7.56" OR (9.84)
MAXIMUM SHIFTING TRAVEL: 3.15" OR (HOB SHIFT 7.87)
HOB SPEED RANGES: 80 –480 RPM OR (HOB SPEED 40-320 RPM)
AXIAL FEEDS, PER REVOLUTION OF WORK:
0090" –.0622" OR (.015-.354 IPR)
RADIAL FEEDS, HYDRAULIC, PER MINUTE:
.0039" – .4724" OR (INFINITELY VARIABLE .028 -.53/MIN.)
TOTAL HP RATING ALL MOTORS: 20 HP
MECHANICAL SPECIFICATIONS:
GEAR HOBBER DIMENSIONS: 115 L x 70 W x 106 H
ELECTRICAL BOX DIMENSIONS: 122 1/2 L x 20 W x 94 1/2 H
MACHINE NET WEIGHT: 21,000 LBS
MACHINE IS EQUIPPED WITH THE FOLLOWING:
DIFFERENTIAL
UNIVERSAL HOB HEAD
HOB SHIFTING DEVICE FOR UNIVERSAL HOB HEAD AND PRECISION HOB SHIFT
POWER CLAMPING
AUTOMATIC FEED CONTROL
MISCELLANEOUS CHANGE GEARS

Description :--